

Tenor[®] AF Series

- 8 Analog line or trunk interfaces
- Up to 8 simultaneous VoIP calls
- Available in Termination or Gateway configurations
- Integrated H.323 gatekeeper and SIP B2BUA for survivability**
- Answer and Disconnect Supervision
- IVR/RADIUS AAA Compliant (Multi-lingual IVR)
- Support for external Quintum Call Routing Server*
- Support for external Quintum Tenor Monitor
- Support for external Remote Management Session Server*



A more intelligent way to implement VoIP in remote offices and SOHO environments

The Quintum[®] Tenor[®] AF Series gives small to medium sized businesses with analog voice infrastructures an easy, cost-effective way to capitalize on the power of Voice over IP (VoIP). The Tenor integrates a gateway, a gatekeeper, and intelligent call routing, and supports QoS all in one solution. The Tenor connects to the data network through a 10/100 Ethernet interface, the voice network through either a PBX or phone, and the public switched telephone network (PSTN).

More intelligence means greater flexibility

The Tenor can intelligently route calls between the IP network and the PBX or PSTN to achieve the best combination of cost and quality. With its Universal Dial Plan, Tenor can support both public and unique private dialing requirements. No other VoIP solution can match this flexibility.

More intelligence means easier installation

The Tenor is the only VoIP solution that can be installed without upgrades to the existing voice or data networks.

More intelligence means less network congestion

With its PacketSaver[™]* Technology, the Tenor reduces bandwidth consumption up to 57%, by combining voice packets from several calls into a single packet to minimize packet overhead.

More intelligence means better management

The Tenor comes with a set of easy to use configuration and management tools, including Tenor Configuration Manager (GUI) and Wizard, and the Tenor Monitor that offers realtime monitoring of alarms, call status and CDRs. Tenors can easily be remotely managed behind NAT firewalls utilizing the Tenor Remote Management Session Server.*

Tenor AF MultiPath Switch

CALL MANAGEMENT FEATURES

- Automatic call type detection: Voice/Modem/Fax
- Answer and Disconnect Supervision
- Trunk group support
- Public and private dial plan support
- User programmable dial plan support
- Forced IP routing and IP port mapping
- Automatic appending and stripping of digits to dialed numbers
- Call Detail Records
- Least Cost Routing with external Quintum VoIP Call Routing Server*
- Type 1 Caller ID/Name Support (Telcordia, ETSI, NTT and DTMF)

TECHNICAL SPECIFICATIONS

Telephony Specifications

- Voice algorithms: G.723.1a, G.729ab, G.711
- Auto codec negotiation
- Fax support: Industry standard T.38 and Group III at 2.4, 4.8, 7.2, 9.6, 14.4 Kbps
- Modem over IP
- Choice of FXS or FXO configurations
- Standard RJ-11 connectors
- Loop Start, Reverse Battery, Battery Disconnect
- Maximum Call Rate: 300 calls/hour

IP Network Specifications

- LAN Interface: Fast Ethernet port (10/100 Base-T)
- Standard RJ-45 Interface (IEEE 802.3) for 10 Base-T or 100 Base-T connections
- DHCP Client
- QoS Support: IP TOS, DiffServ
- Coding: A law, μ law
- Enhanced (Carrier Grade) Echo Cancellation: ITU Rec. G168, up to 128 msec tailsize

VoIP Network Specifications

- H.323 v.3 Gateway and Integrated Gatekeeper
- SIP User Agent (RFC3261 compliant endpoint)
- SIP Back-to-back User Agent (B2BUA)**
- SIP RFC2833 In-band DTMF signaling
- SIP Supplementary Services
- Message Waiting
- SIP Refer Method support
- IVR/RADIUS server support for AAA with integrated multi-lingual IVR
- Adaptive Voice Activity Detection (VAD) with Comfort Noise Generation (CNG)
- Adaptive Jitter Buffer
- Packet Loss Compensation
- NATAccess™
- Security: IP Filtering
- Up to 8 simultaneous VoIP calls
- Support for DNS Addressing

Configuration / Management

- Quintum Tenor Configuration Manager (GUI) for configuration of remote individual Tenors.
- Quintum Tenor Monitor (GUI) for alarm monitoring, call monitoring and CDR monitoring
- SNMPv2 Agent
- Command Line Interface

GENERAL SPECIFICATIONS

Dimensions: 1U High Chassis

W 8 1/4" x H 2" x D 7"

W 21cm x H 5.1cm x D 18.73cm

- Maximum weight: 1.3 lbs. (0.6kg)
- AC Power: 100-240 Volts AC, 50/60 Hz, 22 watts
- Operating temperature: 40° - 104° F (5° - 40° C)
- Operating humidity: 20% - 80% non-condensing
- Telco: FCC Part 68, AS/ACIF S003, CS03, JATE AS/ACIFS002:2001
- EMC: FCC Part 15 Class B, EN55022, EN55024, EN61000-2-3, EN61000-3-3, AS/NZS3260
- Safety: UL60950, EN60950, AS/NZS60950

Tenor AF Series	Termination AFT Series	Station Gateway AFG Series
8 Simultaneous VoIP Calls	8 FXO	8 FXS



* Quintum product purchased separately
** Not supported in initial software release



71 James Way, Eatontown, New Jersey 07724
1-877-SPEAK-IP · Tel 732.460.9000 · Fax 732.544.9119
www.Quintum.com